



CONTROLS

FOR MW RESIDENTIAL & LIGHT COMMERCIAL MONOSPLIT/LIGHT COMMERCIAL/MULTISPLIT R32

140	STANDARD INDIVIDUAL CONTROLS R32
143	INDIVIDUAL CONTROLS R32
144	OPTIONAL CONTROLS R32

FOR VRF SYSTEMS MW MINI - MW 2-PIPE - MW 3-PIPE

145	VRF SYSTEMS WIFI CONTROLS
146	VRF STANDARD INDIVIDUAL CONTROLS
147	VRF OPTIONAL INDIVIDUAL CONTROLS
149	VRF OPTIONAL CENTRALIZED CONTROLS
150	OTHER VRF OPTIONAL CONTROLS

STANDARD INDIVIDUAL CONTROLS **R32**

INFRARED REMOTE CONTROL



Action Remote control included

MONOSPLIT/MULTISPLIT **R32**

FEATURES

- Temperature setting & display.
- Clock.
- 7 fan speed levels.
- ON/OFF Timer.
- Air distribution with automatic vertical and/or horizontal flaps' swinging.
- Autorestart: restart after blackout with restoration of the previous state.

FUNCTIONS

- I-Feel: optimal control of the room temperature based on the temperature detected by the sensor built into the remote control.
- Sleep: automatic control of room temperature during night hours (3 functions).
- X-fan: allows you to dry the evaporator to avoid the formation of mold and bacteria (Airpro Plus).
- Turbo: rapid reaching of room temperature.
- Light: activation/deactivation of display brightness (Airpro Plus).
- Quiet: Silent mode
- Energy saving (Airpro Plus).
- WiFi.
- Cold Plasma: ionizer.

MODES

- Heating.
- Dehumidification.
- Automatic.
- Cooling.
- Ventilation.



Airpro Plus Remote control included

MULTISPLIT **R32**



Remote control included

MULTISPLIT **R32**
8-way compact cassette

LIGHT COMMERCIAL **R32**
8-way compact cassette (up to 3.50 kW)
8-way big cassette floor/ceiling (up to 7.10 kW)

FEATURES

- Clock.
- ON/OFF Timer.
- 4 fan speed levels + Turbo function.
- Air distribution with automatic vertical and/or horizontal flaps' swinging.
- Setting the room temperature and displaying the indoor and outdoor temperature.

FUNCTIONS

- I-Feel.
- Sleep.
- Energy saving (cooling).
- Absence (heating).
- Key lock.
- X-fan: only cooling and dehumidifying.
- Light: enables/disables display lighting.

MODES

- Heating.
- Cooling.
- Dehumidification.
- Ventilation.
- Automatic.

STANDARD INDIVIDUAL CONTROLS **R32**

INFRARED REMOTE CONTROL



Remote control included

MULTISPLIT **R32**
1-way cassette ceiling

FEATURES

- Temperature setting & display.
- Clock.
- ON/OFF Timer.
- 4 fan speed levels: auto, low, medium or high.
- 6 fan speed levels with console remote control: auto, low, medium-low, medium, medium-high or high.
- Air distribution with automatic vertical flaps' swinging.
- Autorestart: restart after blackout with restoration of the previous state.

FUNCTIONS

- I-Feel: optimal control of the room temperature based on the temperature detected by the sensor built into the remote control.
- Sleep: automatic control of room temperature during night hours.
- X-fan: only in cooling and dehumidification.
- Turbo: the unit operates at very high speed to quickly reach the cooling or heating temperature.
- Light: display brightness on/off.
- Quiet: Silent mode.
- Energy saving.
- Key lock.

MODES

- Heating.
- Dehumidification.
- Automatic.
- Cooling.
- Ventilation.



Remote control included

MONOSPLIT **R32**
console



Remote control included

LIGHT COMMERCIAL **R32**
8-way big cassette floor/ceiling
(from 10 to 16 kW)

FEATURES

- Temperature setting & display.
- Clock.
- ON/OFF Timer.
- 4 fan speed levels: auto, low, medium or high.

MODES

- Heating.
- Cooling.
- Dehumidification.
- Ventilation.
- Automatic.

FUNCTIONS

- Follow me: adjusts the room temperature according to that detected by the remote control to obtain maximum comfort.
- Sleep: automatic control of room temperature during night hours.
- Self Clean: allows the evaporator to dry to avoid the formation of mold and bacteria.
- Turbo: the unit operates at very high speed to quickly reach the cooling or heating temperature.
- Led: brightness adjustment.
- Breeze Away: in cooling, ventilation and dehumidification mode, it allows you to avoid a direct air flow.

STANDARD INDIVIDUAL CONTROLS **R32**

WIRED CONTROL



Wired control

STANDARD (included)
for the models
LIGHT COMMERCIAL **R32**
ducted
(up to 7.10 kW)

FEATURES

- Temperature setting & display.
- ON/OFF Timer.
- 5 fan speed levels + auto.

FUNCTIONS

- Sleep: automatic control of room temperature during night hours.
- Turbo: the unit operates at very high speed to quickly reach the cooling or heating temperature.
- X-fan: after the unit has been turned off, it allows the evaporator to dry to prevent the formation of mold and bacteria.
- Key lock.

MODES

- Heating.
- Dehumidification.
- Automatic.
- Cooling.
- Ventilation.

WIRED CONTROL



DMW-W2-ZA Wired control

STANDARD (included)
for the models
LIGHT COMMERCIAL **R32**
ducted
(from 10 to 16 kW)

FEATURES

- LCD Display.
- Error codes display.
- Room temperature display.
- Weekly Timer.

FUNCTIONS

- Follow me.
- Turbo: the unit operates at very high speed to quickly reach the cooling or heating temperature.
- Auto Restart.
- ON/OFF Timer.
- Weekly Timer.

MODES

- Heating.
- Dehumidification.
- Automatic.
- Cooling.
- Ventilation.

INDIVIDUAL CONTROLS **R32**

WIRED CONTROL WITH BUILT-IN WI-FI MODULE



DMW-ZA1-WiFi

Wired control

Optional for the models
LIGHT COMMERCIAL **R32**
8-way compact cassette

Up to 7.10 kW:
8-way big cassette
floor/ceiling,
ducted

CARATTERISTICHE

- Impostazione e visualizzazione della temperatura.
- Timer ON/OFF.
- 5 livelli di velocità del ventilatore + auto.

FUNCTIONS

- Sleep: automatic control of room temperature during night hours.
- Turbo: the unit operates at very high speed to quickly reach the cooling or heating temperature.
- X-fan: after the unit has been turned off, it allows the evaporator to dry to prevent the formation of mold and bacteria.
- Key lock.

MODES

- Heating.
- Dehumidification.
- Automatic.
- Raffrescamento.
- Ventilation.

WIRED CONTROL WITH BUILT-IN WI-FI MODULE



DMW-ZAL-LCAC WiFi

Wired control

STANDARD (included)
for the models
MULTISPLIT **R32**
ducted

Optional for the models
MULTISPLIT **R32**
8-way compact cassette
1-way cassette
ceiling

FEATURES

- Integrated ambient temperature sensor.
- 6 levels of fan speed.
- Error display.
- ON/OFF Timer.
- Memory: restart after blackout with restoration of previous state.

FUNCTIONS

- Sleep: automatic control of room temperature during night hours.
- Turbo: the unit operates at very high speed to quickly reach the cooling or heating temperature.
- Quiet: Silent mode.
- X-fan: it allows the evaporator to dry to prevent the formation of mold and bacteria.
- Absence (heating only): prevents the room temperature from falling below 8° C.
- Key lock.

MODES

- Heating.
- Dehumidification.
- Automatic.
- Cooling.
- Ventilation.

OPTIONAL CONTROLS R32

WIRED CONTROL



M-RF-CW2-L-G

Optional for the models
MULTISPLIT **R32**
wall (Airpro Plus & Action)
console
1-way cassette
compact cassette
ceiling

CARATTERISTICHE

- 4 livelli di velocità del ventilatore: auto, bassa, media o alta.
- Distribuzione dell'aria con oscillazione verticale e orizzontale automatica,
- Visualizzazione errori.
- Timer giornaliero, settimanale o bi-settimanale.
- Memory: restart after blackout with restoration of previous state.

FUNCTIONS

- Sleep: automatic control of room temperature during night hours.
- Turbo: the unit operates at very high speed to quickly reach the cooling or heating temperature.
- Quiet: Silent mode.
- X-Fan: after the unit has been turned off, it allows the evaporator to dry to prevent the formation of mold and bacteria.
- Absence (heating only): prevents the room temperature from falling below 8° C.
- Key lock.

MODES

- Heating.
- Dehumidification.
- Automatic.
- Cooling.
- Ventilation.

WIRED CONTROL WITH BUILT-IN WIFI MODULE



DMW-WIFI-ZA Wired control

optional for the models
LIGHT COMMERCIAL **R32**
ducted 10-16 kW
floor/ceiling 10-16 kW
big cassette 84x84 10-16 kW

FEATURES

- LCD Display.
- Error codes display.
- Room temperature display.
- Weekly Timer.

FUNCTIONS

- Follow me.
- Turbo: the unit operates at very high speed to quickly reach the cooling or heating temperature.
- Auto Restart.
- ON/OFF Timer.
- Weekly Timer.

MODES

- Heating.
- Dehumidification.
- Automatic.
- Cooling.
- Ventilation.

WI-FI CONTROLS FOR VRF SYSTEMS

WI-FI MODULE



M-V-WiFi-2-IDU



EWPE SMART



Available for Android and iOS smartphones and tablets

Some examples of screenshots from iOS devices


M-V-WiFi-2-IDU module for VRF systems

All the main air conditioning settings at your fingertips on your smartphone

MULTIWARM presents the new M-V-WiFi-2-IDU module which allows access to remote control of the air conditioner via an app downloadable on a smartphone.

The MULTIWARM Wi-Fi kit can connect up to 80 indoor units.

Thanks to the M-V-WiFi-2-IDU app, you can manage the main operating parameters from your home with a simple domestic Wi-Fi connection, or away from home, with a simple Internet connection. With EWPE SMART by MULTIWARM, you can turn the air conditioner on, off, adjust the room temperature and air flow, and operate in cooling or heating mode, with just a few "touches" on your mobile phone. An intelligent app that controls comfort and energy savings with a beneficial effect on your bill.



MAIN FUNCTIONS OF THE APP

- > Access security with account protected by credentials (User ID and PWD).
- > Individual control of individual units.
- > Turning on and off.
- > Selecting the operating mode.
- > Adjusting the set temperature.
- > Fan speed.
- > Weekly timer.
- > Heating activation 8° C (function that prevents the room temperature from falling below 8° C).
- > Silent mode.

VRF STANDARD INDIVIDUAL CONTROLS

INFRARED REMOTE CONTROL



M-V-CI-NB1-G

Standard for the following units:

wall, 8-way compact cassette, 8-way cassette, console, floor/ceiling

FEATURES

- Clock.
- Timer.
- 4 fan speed levels + Turbo function.
- Air distribution

with vertical or horizontal flaps' swinging.

- Setting the room temperature and displaying the indoor and outdoor temperature.

FUNCTIONS

- I-Feel.
- Sleep.
- Energy saving (cooling).
- Absence (heating).
- Key lock.
- X-fan.
- Light.

MODES

- Heating.
- Cooling.
- Dehumidification.
- Ventilation.
- Automatic.

WIRED CONTROL



M-V-CW-SD1-G

Standard for the following units:

ducted: low/high static pressure, 100% outdoor air ducted, enthalpy recovery unit, recovery unit with coil, recessed floor unit and EEV kit for AHU

Optional for other units

Touch key panel. Monochrome LCD display with white backlighting, soft touch buttons. Modern design, square lines. Intuitive remote control for the user and versatile thanks to the different functions.

FEATURES

- Clock.
- 24 hour timer for on/off.
- 6 fan speed levels + Turbo function.
- Air distribution with vertical or horizontal flaps' swinging
- Integrated ambient temperature sensor.
- View and set project parameters.
- Receiving infrared signal from the remote control.

FUNZIONI

- Sleep.
- Quiet.
- Auto Quiet.
- X-fan.
- Light.
- Defrost.
- Save.
- Absence (heating).
- Key lock.
- Memory.
- Filter cleaning reminder.

MODES

- Heating.
- Cooling.
- Dehumidification.
- Ventilation.
- Automatic.

UP TO 16 INDOOR UNITS CAN BE CONNECTED, WHICH WILL OPERATE WITH THE SAME SETTINGS

See details of functions and application types, page 148

VRF OPTIONAL INDIVIDUAL CONTROLS

WIRED CONTROL FOR HOTEL



M-V-CW-HB2-G
Optional for all
types of indoor
units

Simplified panel particularly suitable for hotel applications. Backlit monochrome LCD display, mechanical buttons. Modern design, square lines, with glossy glass effect front panel. Very simple and intuitive remote control for the user and with simplified functions. Possible connection with automatic access management systems.

FEATURES

- 6 fan speed levels + Turbo function.
- Air distribution with vertical flaps' swinging.
- Setting and displaying the room temperature.
- Receiving infrared signal from the remote control.

FUNCTIONS

- Defrost.
- Key lock.
- Memory.

MODES

- Heating.
- Cooling.
- Dehumidification.
- Ventilation.
- Automatic.

UP TO 16 INDOOR UNITS CAN BE CONNECTED, WHICH WILL OPERATE WITH THE SAME SETTINGS

SMART WIRED CONTROL



M-V-CW-TW1-G
Optional for all
types of indoor
units

Smart touch screen panel with high resolution LCD display. Elegant design, square lines. Very advanced remote control complete with various functions, each viewable on a single interactive screen and easy to manage.

FEATURES

- Clock.
- 3 types of Weekly Timer.
- 6 fan speed levels + Turbo function.
- Air distribution with vertical or horizontal flaps' swinging.
- Detection and display of ambient temperature.
- Receiving infrared signal from the remote control.
- Various customizations possible such as light regulation and stand-by time.

FUNCTIONS

- Sleep.
- Quiet.
- Auto Quiet.
- X-fan.
- Light.
- Defrost.
- Save.
- Absence (heating).
- Key lock.
- Memory.
- Filter cleaning reminder.

MODES

- Heating.
- Cooling.
- Dehumidification.
- Ventilation.
- Automatic.

UP TO 16 INDOOR UNITS CAN BE CONNECTED, WHICH WILL OPERATE WITH THE SAME SETTINGS

See details of functions and application types, page 148

Application types for VRF wired controls

M-V-CW-SD1-G
M-V-CW-HB2-G
M-V-CW-TW1-G

pag. 146-147

SINGLE CONTROL FOR THE MANAGEMENT OF A SINGLE INDOOR UNIT

Each indoor unit has its own independent control.

TWO CONTROLS FOR MANAGING A SINGLE UNIT

An indoor unit can be controlled by two wired controllers placed in different locations (Master/Slave mode).

SINGLE CONTROL FOR MANAGING MULTIPLE INDOOR UNITS (GROUP CONTROL)

A single wired controller can control up to 16 indoor units simultaneously.

TWO CONTROLS FOR MANAGING DIFFERENT INDOOR UNITS

The indoor units (maximum 16) can be managed by two wired controllers simultaneously.

Appendix

DETAIL OF CONTROL FUNCTIONS

- **Absence (heating only):** prevents the room temperature from falling below 8° C.
- **Defrost:** defrost function.
- **Energy saving/Save:** energy saving.
- **I Feel:** adjusts the room temperature according to that detected by the remote control to obtain maximum comfort.
- **Light:** brightness adjustment.
- **Memory:** in the event of a blackout, when the power is restored, it automatically restarts with the previous settings.
- **Quiet/Auto Quiet:** Silent mode.
- **Rapid:** when the unit is turned on, in direct expansion cooling or heating mode, it allows the set temperature to be reached quickly, improving indoor comfort.
- **Sleep:** night operation.
- **Turbo:** the unit operates at very high speed to quickly reach the cooling or heating temperature.
- **X-Fan:** allows the evaporator to dry to avoid the formation of mold and bacteria.

VRF OPTIONAL CENTRALIZED CONTROLS



M-V-CC-T32-G

Simplified centralized panel with 4.3" LCD touch screen display. Modern and elegant design. Small footprint: recessed wall installation with a protrusion of only 11 mm.

You can manage up to 32 groups of indoor units (32 indoor units in total) distributed across up to 16 systems*. Possibility to: assign names to indoor units, select icons and create custom settings (background, backlight).

FEATURES

- View and set project parameters.
- Fault recording and access management.

FUNCTIONS

- Single unit control: temperature setting, timer, fan speed, air distribution control with vertical or horizontal flaps' swinging and advanced functions (sleep, quiet, auto quiet, auxiliary heating, save, rapid, absence in heating).
- Group management.
- Centralized control of all indoor units.

MODES

- Heating.
- Hydronic heating.
- 3D heating.
- Ambient heating.
- Cooling.
- Dehumidification.
- Ventilation.
- Automatic.



M-V-CC-T255-G

Centralized Touch Screen Panel. High resolution 1280x800 7" touch screen LCD display. Modern and elegant design. User-friendly operation. Small footprint: recessed wall installation with a protrusion of only 11 mm.

You can manage up to 255 groups of indoor units (255 indoor units in total) distributed across up to 16 systems*. Possibility to: assign names to indoor units, select icons and create custom settings (background, backlight).

FEATURES

- View and set project parameters.
- Fault recording and access management.
- Programming (setting different programs).
- Maintain settings in the event of a blackout.

FUNCTIONS

- Single unit control: temperature setting, timer, fan speed, air distribution control with vertical or horizontal flaps' swinging and advanced functions (sleep, quiet, auto quiet, auxiliary heating, save, rapid, absence in heating).
- Group management.
- Centralized control of all indoor units.

MODES

- Heating.
- Hydronic heating.
- 3D heating.
- Ambient heating.
- Cooling.
- Dehumidification.
- Ventilation.
- Automatic.

* When the centralized controls are connected to multiple outdoor units in combination, insert the 120Ω electrical resistance and use a twisted and shielded cable.

OTHER VRF OPTIONAL CONTROLS

WEB-BASED MONITORING SOFTWARE



M-V-SOFT-Mon
Optional for all
types of indoor
units
(requires Gateway
M-V-Gateway-Mon)



M-V-Gateway-Mon
TCP/IP Network
Gateway

Remote control of on, off, temperature setting, operating mode and other parameters of any type of indoor unit or group of indoor units.

- Real-time monitoring of system status and output of data for any errors and malfunctions.
- Programming of units according to user needs and the intended use of the building.
- Visualized graphical representation of the system structure and control modes of individual devices and/or groups of the entire project.
- Consumption accounting.

GATEWAY FOR BACNET/IP AND MODBUS RTU/TCP MAX 255 I.U.



M-V-Gateway-LAN/Bacnet
Optional for all
types of indoor
units
(max. 16 systems or
255 indoor units)

- Network gateway that supports connection to a building management system (BMS).
- This network gateway features BACnet and Modbus communication protocols.
- The high-efficiency, large-data communication system can monitor unit operation in real time and control up to 255 indoor units simultaneously.

MINI GATEWAY FOR MODBUS RTU



M-V-Gateway-Modbus
Optional for all
types of indoor
units
(max. 16 systems or
128 indoor units)

- The mini Modbus network gateway enables connection to a building management system (BMS).
- Remote control for single unit or groups of units for switching on, off, setting temperature, operating mode, fan speed, control lock with individual remote controls and real-time monitoring of operating parameters and error codes of the units.

OTHER VRF OPTIONAL CONTROLS

GATEWAY FOR CONNECTING LIGHT COMMERCIAL UNITS TO THE CENTRALIZED CONTROL



DMC-LCAC-Gateway

**For light commercial units up to 7.1kW
ducted, compact cassette, cassette
84x84, floor/ceiling.**

One gateway is required for each indoor unit (up to 255 gateways for each centralized control).

Interface to control light commercial R32 units up to 7.1kW via the M-V-CG-T255-G centralized control.