

## INDOOR UNITS

## 4 CAPACITIES

2.60~7.20 kW

## 7 SPEED LEVELS

of ventilation



I-FEEL FUNCTION

SELF-CLEAN FUNCTION

COLD PLASMA FILTER

REMOTE CONTROL INCLUDED

## WALL ACTION



| Model                                                  |             |       | MKEGM 267 ZAL               | MKEGM 357 ZAL               | MKEGM 537 ZAL                | MKEGM 717 ZAL                |
|--------------------------------------------------------|-------------|-------|-----------------------------|-----------------------------|------------------------------|------------------------------|
| Type                                                   |             |       | Wall type indoor unit       |                             |                              |                              |
| Control                                                |             |       | Remote control              |                             |                              |                              |
| Nominal capacity                                       | Cooling     | kW    | 2.60                        | 3.50                        | 5.00                         | 7.20                         |
|                                                        | Heating     | kW    | 2.80                        | 3.80                        | 5.60                         | 8.50                         |
| Electrical data                                        |             |       |                             |                             |                              |                              |
| Power supply                                           | Ph-V-Hz     |       | -                           | -                           | -                            | -                            |
| Connection wires between I.U. and O.U.                 | no.         |       | 4                           | 4                           | 4                            | 4                            |
| Refrigerant circuit data                               |             |       |                             |                             |                              |                              |
| Liquid/gas refrigerant pipe diameter                   | mm (inches) |       | ø6.35(1/4") / ø9.52(3/8")   | ø6.35(1/4") / ø9.52(3/8")   | ø6.35(1/4") / ø9.52(3/8")    | ø6.35(1/4") / ø12.74(1/2")   |
| Product specifications                                 |             |       |                             |                             |                              |                              |
| Dimensions                                             | LxDxH       | mm    | 708x185x260                 | 835x200x275                 | 943x246x333                  | 943x246x333                  |
|                                                        | Net weight  | Kg    | 7                           | 9                           | 13                           | 13.5                         |
| Sound power level                                      | Hi~Lo       | dB(A) | 55/48/46/44/40/37/33        | 59/50/47/45/41/38/35        | 60/58/56/54/48/44/41         | 65/56/54/52/50/46/42         |
| Sound pressure level                                   | Hi~Lo       | dB(A) | 38/36/34/32/28/25/21        | 42/38/35/33/29/26/23        | 47/45/43/41/35/30/28         | 50/46/44/42/40/36/32         |
| Volume of air treated                                  | Hi~Lo       | m³/h  | 500/470/430/390/320/270/250 | 650/550/470/420/380/350/310 | 1000/960/870/810/720/640/600 | 1050/900/740/690/640/590/540 |
| Optional parts                                         |             |       |                             |                             |                              |                              |
| Individual wired control                               |             |       | M-RF-CW2-L-G                |                             |                              |                              |
| Wired control for centralized control                  |             |       | M-RF-CW3-L-G                |                             |                              |                              |
| Wi-Fi module                                           |             |       | Integrated                  |                             |                              |                              |
| Centralized control (only possible with wired control) |             |       | M-V-CC-T255-G               |                             |                              |                              |

## 4 CAPACITIES

2.60~7.20 kW

## ELEGANT &amp; COMPACT DESIGN

210 mm depth for the 2.60 and 3.50 kW models



## MAXIMUM SILENCE

only 22 dB(A) in Low mode for the 2.60 kW model

I-FEEL FUNCTION

COLD PLASMA FILTER

REMOTE CONTROL INCLUDED

## WALL AIRPRO PLUS



| Model                                                  |             |       | MKEGM 265 ZAL               | MKEGM 355 ZAL               | MKEGM 535 ZAL               | MKEGM 715 ZAL                  |
|--------------------------------------------------------|-------------|-------|-----------------------------|-----------------------------|-----------------------------|--------------------------------|
| Type                                                   |             |       | Wall-mounted indoor unit    |                             |                             |                                |
| Control                                                |             |       | Remote control              |                             |                             |                                |
| Nominal capacity                                       | Cooling     | kW    | 2,60                        | 3,50                        | 5,00                        | 7,20                           |
|                                                        | Heating     | kW    | 2,80                        | 3,80                        | 5,60                        | 8,50                           |
| Electrical data                                        |             |       |                             |                             |                             |                                |
| Power supply                                           | Ph-V-Hz     |       | -                           | -                           | -                           | -                              |
| Connection wires between I.U. and O.U.                 | no.         |       | 4                           | 4                           | 4                           | 4                              |
| Refrigerant circuit data                               |             |       |                             |                             |                             |                                |
| Liquid/gas refrigerant pipe diameter                   | mm (inches) |       | ø6,35(1/4") / ø9,52(3/8")   | ø6,35(1/4") / ø9,52(3/8")   | ø6,35(1/4") / ø12,74(1/2")  | ø6,35(1/4") / ø15,9(5/8")      |
| Product specifications                                 |             |       |                             |                             |                             |                                |
| Dimensions                                             | LxDxH       | mm    | 865x290x210                 | 865x290x210                 | 996x301x225                 | 1101x327x249                   |
|                                                        | Net weight  | Kg    | 10,5                        | 10,5                        | 13                          | 16                             |
| Sound power level                                      | Hi~Lo       | dB(A) | 58/52/50/48/44/40/36        | 58/53/51/49/46/43/37        | 60/57/55/54/52/50/46        | 64/59/56/55/53/51/48           |
| Sound pressure level                                   | Hi~Lo       | dB(A) | 41/38/36/34/30/26/22        | 43/39/37/35/32/29/23        | 43/41/39/37/35/32/31        | 48/44/41/40/38/36/33           |
| Volume of air treated                                  | Hi~Lo       | m³/h  | 660/590/540/490/450/420/390 | 680/590/540/490/450/420/390 | 850/750/680/610/570/520/460 | 1250/1100/1000/950/900/850/800 |
| Optional parts                                         |             |       |                             |                             |                             |                                |
| Individual wired control                               |             |       | M-RF-CW2-L-G                |                             |                             |                                |
| Wired control for centralized control                  |             |       | M-RF-CW3-L-G                |                             |                             |                                |
| Wi-Fi module                                           |             |       | Integrated                  |                             |                             |                                |
| Centralized control (only possible with wired control) |             |       | M-V-CC-T255-G               |                             |                             |                                |