

100% OUTDOOR AIR DUCTED

2 CAPACITIES
12.50~14.00 kW

WASHABLE FILTER
better air quality

All-air ducting allows fresh outside air to be introduced into the rooms without causing fluctuations in internal temperature.

CONTROLS
wired control included

M-V-DFA-12520~14020-G



Model			M-V-DFA-12520-G	M-V-DFA-14020-G
Control (included)			Wired control	
Rated capacity	Cooling ¹	kW	12.50	14.00
	Heating ²	kW	8.50	10.00
Electrical data				
Power supply		Ph-V-Hz	1-220~240V-50Hz	
Power absorption		W	200/350	200/350
Product specifications				
Dimensions	WxHxD	mm	1400x300x700	1400x300x700
Net weight		Kg	54	54
Sound pressure level at 1 m	H/M/L	dB(A)	46/50	46/50
Volume of air treated	H/M/L	m³/h	1200/2000	1200/2000
Fan static pressure	Std/Max	Pa	150/200	150/200
Connection diameter	Liquid/Gas	mm (inch)	9.52 (3/8") / 15.9 (5/8")	
	Condensate	mm	25	25
Application field (suctioned air temp.)		°C	-7~45 BS	
Optional parts				
Centralized control			M-V-CC-T255-G / M-V-CC-T32-G	

1. Conditions: intake air 35°C DB (28°C WB), delivery air 18°C.

2. Conditions: intake air 7°C DB (6°C WB), delivery air 22°C.