

# DUCTED HIGH STATIC PRESSURE

**8 CAPACITIES**

7.10~28.00 kW

**WASHABLE FILTER**

better air quality

Ideal for cooling and heating medium and large sized rooms

**CONTROLS**

wired control included

**ULTRA COMPACT DESIGN**only **300 mm** high for the 7.10 and 18.00 kW models**CONDENSATE DRAIN PUMP INCLUDED**maximum height difference **1100 mm** from the outlet hole for models from 7.10 to 18.00 kW**5 FAN SPEEDS**

auto, low, med, high, turbo



M-V-DHA-711~1801-G



M-V-DHA-224~280-G



| Model                         |            |           | M-V-DHA-711-G                             | M-V-DHA-901-G  | M-V-DHA-1121-G | M-V-DHA-1401-G |
|-------------------------------|------------|-----------|-------------------------------------------|----------------|----------------|----------------|
| Control (included)            |            |           | Wired control                             |                |                |                |
| Rated capacity                | Cooling    | kW        | 7.10                                      | 9.00           | 11.20          | 14.00          |
|                               | Heating    | kW        | 8.00                                      | 10.00          | 12.50          | 16.00          |
| <b>Electrical data</b>        |            |           | 1-220~240V-50Hz                           |                |                |                |
| Power supply                  |            | Ph-V-Hz   |                                           |                |                |                |
| Power absorption              |            | W         | 100                                       | 140            | 160            | 220            |
| <b>Product specifications</b> |            |           |                                           |                |                |                |
| Dimensions                    | WxHxD      | mm        | 1000x300x700                              | 1400x300x700   | 1400x300x700   | 1400x300x700   |
| Net weight                    |            | Kg        | 43                                        | 57             | 57             | 58             |
| Sound pressure level at 1 m   | H/M/L      | dB(A)     | 38/36/34                                  | 40/37/35       | 40/38/36       | 42/39/37       |
| Volume of air treated         | H/M/L      | m³/h      | 1250/1050/950                             | 1800/1450/1250 | 2000/1600/1400 | 2350/1900/1650 |
| Fan static pressure           | Std/Max    | Pa        | 90/200                                    | 90/200         | 90/200         | 90/200         |
| Connection diameter           | Liquid/Gas | mm (inch) | 9.52 (3/8") / 15.9 (5/8")                 |                |                |                |
|                               | Condensate | mm        | 25                                        | 25             | 25             | 25             |
| <b>Optional parts</b>         |            |           | M-V-CC-T255-G / M-V-CC-T32-G (simplified) |                |                |                |
| Centralized control           |            |           |                                           |                |                |                |

| Model                         |            |           | M-V-DHA-1601-G                            | M-V-DHA-1801-G | M-V-DHA-224-G  | M-V-DHA-280-G  |
|-------------------------------|------------|-----------|-------------------------------------------|----------------|----------------|----------------|
| Control (included)            |            |           | Wired control                             |                |                |                |
| Rated capacity                | Cooling    | kW        | 16.00                                     | 18.00          | 22.40          | 28.00          |
|                               | Heating    | kW        | 18.00                                     | 20.00          | 25.00          | 31.00          |
| <b>Electrical data</b>        |            |           | 1-220~240V-50Hz                           |                |                |                |
| Power supply                  |            | Ph-V-Hz   |                                           |                |                |                |
| Power absorption              |            | W         | 230                                       | 350            | 800            | 900            |
| <b>Product specifications</b> |            |           |                                           |                |                |                |
| Dimensions                    | WxHxD      | mm        | 1400x300x700                              | 1400x300x700   | 1483x385x791   | 1686x450x870   |
| Net weight                    |            | Kg        | 58                                        | 58             | 82             | 105            |
| Sound pressure level at 1 m   | H/M/L      | dB(A)     | 44/41/38                                  | 49/47/44       | 54/52/49       | 55/52/50       |
| Volume of air treated         | H/M/L      | m³/h      | 2500/2000/1750                            | 3000/2600/2000 | 4000/3600/3200 | 4400/4000/3600 |
| Fan static pressure           | Std/Max    | Pa        | 90/200                                    | 90/170         | 100/200        | 100/200        |
| Connection diameter           | Liquid/Gas | mm (inch) | 9.52 (3/8") / 19.05 (3/4")                |                |                |                |
|                               | Condensate | mm        | 25                                        | 25             | 25             | 25             |
| <b>Optional parts</b>         |            |           | M-V-CC-T255-G / M-V-CC-T32-G (simplified) |                |                |                |
| Centralized control           |            |           |                                           |                |                |                |