8-WAY COMPACT CASSETTE 60x60

6 CAPACITIES
1.50~5.60 kW

COMPACT DESIGN
265 mm height for recessed installation in false ceilings

360° AIR DISTRIBUTION

INDIVIDUAL DEFLECTORS CONTROL
for better airflow management

WASHABLE FILTER
better air quality

CONDENSATE DRAIN PUMP INCLUDED
maximum height difference **1200 mm** from panel edge

CONTROLS
standard remote control
optional wired control

M-V-CSA-151~561-G

Wi-Fi
(optional)

Model			M-V-CSA-151-G	M-V-CSA-221-G	M-V-CSA-281-G
Control (included)			Remote control		
Rated capacity	Cooling	kW	1.50	2.20	2.80
	Heating	kW	1.80	2.50	3.20
Electrical data					
Power supply		Ph-V-Hz	1-220~240V-50Hz		
Power absorption		W	30	30	30
Product specifications					
Dimensions	WxHxD	mm	570x265x570	570x265x570	570x265x570
Net weight		Kg	17.5	17.5	17.5
Sound pressure level at 1 m	H/M/L	dB(A)	33/30/25	36/31/25	36/33/28
Volume of air treated	H/M/L	m3/h	460/420/370	500/460/370	570/480/420
Connection diameter	Liquid/Gas	mm (inch)	6.35 (1/4") / 9.52 (3/8")		
	Condensate	mm	25	25	25
Accessories					
Decorative panel			M-V-CGR-608-G		
Panel dimensions	WxHxD	mm	620x47.5x620	620x47.5x620	620x47.5x620
Net weight		Kg	3	3	3
Optional parts					
Wired control			M-V-CW-SD1-G (LCD) / M-V-CW-TW1-G (touch) / M-V-CW-HB1-G (simplified)		
Centralized control			M-V-CC-T255-G / M-V-CC-T32-G (simplified)		

Model			M-V-CSA-361-G	M-V-CSA-451-G	M-V-CSA-561-G
Control (included)			Remote control		
Rated capacity	Cooling	kW	3.60	4.50	5.60
	Heating	kW	4.00	5.00	6.30
Electrical data					
Power supply		Ph-V-Hz	1-220~240V-50Hz		
Power absorption		W	30	45	45
Product specifications					
Dimensions	WxHxD	mm	570x265x570	570x265x570	570x265x570
Net weight		Kg	17.5	17.5	17.5
Sound pressure level at 1 m	H/M/L	dB(A)	39/37/35	43/41/39	43/41/39
Volume of air treated	H/M/L	m3/h	620/550/480	730/650/560	730/650/560
Connection diameter	Liquid/Gas	mm (inch)	6.35 (1/4") / 12.74 (1/2")		9.52 (3/8") / 15.9 (5/8")
	Condensate	mm	25	25	25
Accessories					
Decorative panel			M-V-CGR-608-G		
Panel dimensions	WxHxD	mm	620x47.5x620	620x47.5x620	620x47.5x620
Net weight		Kg	3	3	3
Optional parts					
Wired control			M-V-CW-SD1-G (LCD) / M-V-CW-TW1-G (touch) / M-V-CW-HB1-G (simplified)		
Centralized control			M-V-CC-T255-G / M-V-CC-T32-G (simplified)		