

WALL

7 CAPACITIES

1.50~7.10 kW

ELEGANT & COMPACT DESIGN

209 mm depth for models from 1.50 to 3.60 kW

WASHABLE FILTER

better air quality

SELF-DIAGNOSIS

CONTROLS

standard remote control

optional wired control

M-V-WLA-151~711-G



Model			M-V-WLA-151-G	M-V-WLA-221-G	M-V-WLA-281-G
Control (included)			Remote control		
Rated capacity	Cooling	kW	1.50	2.20	2.80
	Heating	kW	1.80	2.50	3.20
Electrical data					
Power supply		Ph-V-Hz	1-220~240V-50Hz		
Power absorption		W	20	20	20
Product specifications					
Dimensions	WxHxD	mm	845x289x209	845x289x209	845x289x209
Net weight		Kg	10.5	10.5	10.5
Sound pressure level at 1 m	H/M/L	dB(A)	35/33/30	35/33/30	35/33/30
Volume of air treated	H/M/L	m³/h	500/440/300	500/440/300	500/440/300
Connection diameter	Liquid/Gas	mm (inch)	6.35 (1/4") / 9.52 (3/8")		
	Condensate	mm	20	20	20
Optional parts					
Wired control			M-V-CW-SD1-G (LCD) / M-V-CW-TW1-G (touch) / M-V-CW-HB1-G (simplified)		
Centralized control			M-V-CC-T255-G / M-V-CC-T32-G (simplified)		

Model			M-V-WLA-361-G	M-V-WLA-451-G	M-V-WLA-561-G	M-V-WLA-711-G
Control (included)			Remote control			
Rated capacity	Cooling	kW	3.60	4.50	5.60	7.10
	Heating	kW	4.00	5.00	6.30	7.50
Electrical data						
Power supply		Ph-V-Hz	1-220~240V-50Hz			
Power absorption		W	25	35	50	65
Product specifications						
Dimensions	WxHxD	mm	845x289x209	970x300x224	1078x325x246	1078x325x246
Net weight		Kg	10.5	12.5	16	16
Sound pressure level at 1 m	H/M/L	dB(A)	38/35/31	43/40/37	43/41/37	44/41/37
Volume of air treated	H/M/L	m³/h	630/460/320	850/580/500	1100/850/650	1200/850/650
Connection diameter	Liquid/Gas	mm (inch)	6.35 (1/4") / 12.74 (1/2")		9.52 (3/8") / 15.9 (5/8")	
	Condensate	mm	20	20	20	20
Optional parts						
Wired control			M-V-CW-SD1-G (LCD) / M-V-CW-TW1-G (touch) / M-V-CW-HB1-G (simplified)			
Centralized control			M-V-CC-T255-G / M-V-CC-T32-G (simplified)			