

# RECESSED FLOOR

## 6 CAPACITIES

2.20~7.10 kW

## COMPACT DESIGN

200 mm depth on all capacities

## WASHABLE FILTER

better air quality

M-V-FYA-221~711-G



(optional)

| Model                         |            |           | M-V-FYA-221-G                             | M-V-FYA-281-G | M-V-FYA-361-G            |
|-------------------------------|------------|-----------|-------------------------------------------|---------------|--------------------------|
| Control (included)            |            |           | Wired control                             |               |                          |
| Rated capacity                | Cooling    | kW        | 2.20                                      | 2.80          | 3.60                     |
|                               | Heating    | kW        | 2.50                                      | 3.20          | 4.00                     |
| <b>Electrical data</b>        |            |           |                                           |               |                          |
| Power supply                  |            | Ph-V-Hz   | 1-220~240V-50Hz                           |               |                          |
| Power absorption              |            | W         | 35                                        | 35            | 43                       |
| <b>Product specifications</b> |            |           |                                           |               |                          |
| Dimensions                    | WxHxD      | mm        | 700x615x200                               | 700x615x200   | 700x615x200              |
| Net weight                    |            | Kg        | 23                                        | 23            | 23                       |
| Sound pressure level at 1 m   | H/M/L      | dB(A)     | 30/28/25                                  | 30/28/25      | 33/31/28                 |
| Volume of air treated         | H/M/L      | m³/h      | 450/350/250                               | 450/350/250   | 550/450/350              |
| Fan static pressure           | Std/Max    | Pa        | 10/40                                     | 10/40         | 10/40                    |
| Connection diameter           | Liquid/Gas | mm (inch) | 6.35 (1/4) / 9.52 (3/8)                   |               | 6.35 (1/4) / 12.74 (1/2) |
|                               | Condensate | mm        | 25                                        | 25            | 25                       |
| <b>Optional parts</b>         |            |           |                                           |               |                          |
| Centralized control           |            |           | M-V-CC-T255-G / M-V-CC-T32-G (simplified) |               |                          |

| Model                         |            |           | M-V-FYA-451-G                             | M-V-FYA-561-G | M-V-FYA-711-G |
|-------------------------------|------------|-----------|-------------------------------------------|---------------|---------------|
| Control (included)            |            |           | Wired control                             |               |               |
| Rated capacity                | Cooling    | kW        | 4.50                                      | 5.60          | 7.10          |
|                               | Heating    | kW        | 5.00                                      | 6.30          | 8.00          |
| <b>Electrical data</b>        |            |           |                                           |               |               |
| Power supply                  |            | Ph-V-Hz   | 1-220~240V-50Hz                           |               |               |
| Power absorption              |            | W         | 45                                        | 80            | 90            |
| <b>Product specifications</b> |            |           |                                           |               |               |
| Dimensions                    | WxHxD      | mm        | 900x615x200                               | 1100x615x200  | 1100x615x200  |
| Net weight                    |            | Kg        | 27                                        | 32            | 32            |
| Sound pressure level at 1 m   | H/M/L      | dB(A)     | 33/31/28                                  | 35/33/30      | 37/35/33      |
| Volume of air treated         | H/M/L      | m³/h      | 650/500/400                               | 900/750/600   | 1100/900/700  |
| Fan static pressure           | Std/Max    | Pa        | 15/60                                     | 15/60         | 15/60         |
| Connection diameter           | Liquid/Gas | mm (inch) | 9.52 (3/8) / 15.9 (5/8)                   |               |               |
|                               | Condensate | mm        | 25                                        | 25            | 25            |
| <b>Optional parts</b>         |            |           |                                           |               |               |
| Centralized control           |            |           | M-V-CC-T255-G / M-V-CC-T32-G (simplified) |               |               |