

INDOOR UNITS

3 CAPACITIES
2.60~5.00 kW

7 FAN SPEED levels

ELEGANT & COMPACT DESIGN
215 mm deep



MEMORY FUNCTION, I-FEEL FUNCTION, X-FAN FUNCTION

DOUBLE AIR DELIVERY

8° C HEATING

REMOTE CONTROL INCLUDED



Wi-Fi INTEGRATED

CONSOLE

Model	MFIGM 261 ZAL		MFIGM 351 ZAL		MFIGM 531 ZAL	
Type	Console type indoor unit					
Control	Remote control					
Nominal capacity	Cooling	kW	2.60	3.50	5.00	
	Heating	kW	2.80	3.80	5.60	
Electrical data						
Power supply	Ph-V-Hz	-	-	-	-	
Connection wires between I.U. and O.U.	no.	4	4	4		
Refrigerant circuit data						
Liquid/gas refrigerant pipe diameter	mm (inches)	ø6.35(1/4") / ø9.52(3/8")		ø6.35(1/4") / ø9.52(3/8")		ø6.35(1/4") / ø12.74(1/2")
Product specifications						
Dimensions	LxDxH	mm	700x215x600		700x215x600	
	Net weight	Kg	15.5		16	
Sound power level	Hi~Lo	dB(A)	52/48/46/44/41/38/35		60/58/56/53/51/48/43	
Sound pressure level	Hi~Lo	dB(A)	39/36/34/32/29/26/23		44/40/38/36/33/29/25	
Volume of air treated	Hi~Lo	m ³ /h	500/430/410/370/330/280/250		600/520/480/440/400/360/280	
Optional parts						
Individual wired control			M-RF-CW2-L-G / M-RF-CW3-L-G			
Wi-Fi module			Included			

2 CAPACITIES
3.50~5.00 kW

COMPACT DESIGN
265 mm height for recessed installation in false ceilings

MEMORY FUNCTION

COMPACT CASSETTE



TOP

1000

Built-in condensate drain pump, with the highest discharge head (maximum lift) compared with all competitors in its market segment.

WASHABLE FILTER

X-FAN

TOTAL TEMPERATURE CONTROL

REMOTE CONTROL INCLUDED



Wired remote control with optional integrated Wi-Fi

Model	MTFGM 351 ZL		MTFGM 531 ZL	
Type	Cassette type indoor unit			
Control	Remote control			
Nominal capacity	Cooling	kW	3.50	5.00
	Heating	kW	3.80	5.60
Electrical data				
Power supply	Ph-V-Hz	-	-	
Connection wires between I.U. and O.U.	no.	4	4	
Refrigerant circuit data				
Liquid/gas refrigerant pipe diameter	mm (inches)	ø6.35(1/4") / ø9.52(3/8")		ø6.35(1/4") / ø12.74(1/2")
Product specifications				
Dimensions	LxDxH	mm	570x570x265	
	Net weight	Kg	17	
Sound power level	Hi~Lo	dB(A)	57/55/52/50/48/46/44	
Sound pressure level	Hi~Lo	dB(A)	41/39/36/34/32/30/28	
Volume of air treated	Hi~Lo	m ³ /h	560/540/490/450/420/380/350	
Accessories				
Decorative panel	MTFPG 350 ZA			
Optional parts				
Individual wired control with connection cable	M-RF-CW2-L-G + CW2-SE-TF-ADAPTOR			
Wired control for centralized control	M-RF-CW3-L-G			
Wired control with integrated Wi-Fi module	DMW-ZAL-LCAC WiFi			
Centralized control (only possible with wired control)	M-V-CC-T255-G2			