

# 8-WAY COMPACT CASSETTE 60x60

**6 CAPACITIES**  
1.50~5.60 kW

**COMPACT DESIGN**  
**265 mm** height for recessed installation in false ceilings

**360° AIR DISTRIBUTION**

**WASHABLE FILTER**  
better air quality

**CONDENSATE DRAIN PUMP INCLUDED**

maximum height difference  
**1200 mm** from panel edge

**CONTROLS**  
standard remote control  
optional wired control

M-V-CSA-151~561-G



Model			M-V-CSA-151-G	M-V-CSA-221-G	M-V-CSA-281-G
Control (included)				Remote control	
Rated capacity	Cooling	kW	1.50	2.20	2.80
	Heating	kW	1.80	2.50	3.20
<b>Electrical data</b>					
Power supply		Ph-V-Hz	1-220~240V-50Hz		
Power absorption		W	30	30	30
<b>Product specifications</b>					
Dimensions	WxHxD	mm	570x265x570	570x265x570	570x265x570
Net weight		Kg	17.5	17.5	17.5
Sound pressure level at 1 m	H/M/L	dB(A)	33/30/25	36/31/25	36/33/28
Volume of air treated	H/M/L	m³/h	460/420/370	500/460/370	570/480/420
Connection diameter	Liquid/Gas	mm (inch)	6.35 (1/4") / 9.52 (3/8")		
	Condensate	mm	25	25	25
<b>Accessories</b>					
<b>Decorative panel</b>			<b>M-V-CGR-608-G</b>		
Panel dimensions	WxHxD	mm	620x47.5x620	620x47.5x620	620x47.5x620
Net weight		Kg	3	3	3
<b>Optional parts</b>					
Wired control			M-V-CW-SD1-G (LCD) / M-V-CW-TW1-G (touch) / M-V-CW-HB2-G (simplified)		
Centralized control			M-V-CC-T255-G2 / M-V-CC-T32-G (simplified)		

Model			M-V-CSA-361-G	M-V-CSA-451-G	M-V-CSA-561-G
Control (included)				Remote control	
Rated capacity	Cooling	kW	3.60	4.50	5.60
	Heating	kW	4.00	5.00	6.30
<b>Electrical data</b>					
Power supply		Ph-V-Hz	1-220~240V-50Hz		
Power absorption		W	30	45	45
<b>Product specifications</b>					
Dimensions	WxHxD	mm	570x265x570	570x265x570	570x265x570
Net weight		Kg	17.5	17.5	17.5
Sound pressure level at 1 m	H/M/L	dB(A)	39/37/35	43/41/39	43/41/39
Volume of air treated	H/M/L	m³/h	620/550/480	730/650/560	730/650/560
Connection diameter	Liquid/Gas	mm (inch)	6.35 (1/4") / 12.74 (1/2")		
	Condensate	mm	25	25	25
<b>Accessories</b>					
<b>Decorative panel</b>			<b>M-V-CGR-608-G</b>		
Panel dimensions	WxHxD	mm	620x47.5x620	620x47.5x620	620x47.5x620
Net weight		Kg	3	3	3
<b>Optional parts</b>					
Wired control			M-V-CW-SD1-G (LCD) / M-V-CW-TW1-G (touch) / M-V-CW-HB2-G (simplified)		
Centralized control			M-V-CC-T255-G2 / M-V-CC-T32-G (simplified)		