

CONSOLE

5 CAPACITIES

2.20~5.00 kW

LOW SOUND IMPACT

only **27 dB(A)** for the 2.20 and 2.80 kW models

SELF-DIAGNOSIS

I FEEL FUNCTION

CONTROLS

remote control included
optional wired control

M-V-CNA-22~50-G



Model			M-V-CNA-22-G		M-V-CNA-28-G	
Control (included)			Remote control			
Rated capacity	Cooling	kW	2.20		2.80	
	Heating	kW	2.50		3.20	
Electrical data						
Power supply		Ph-V-Hz	1-220~240V-50Hz			
Power absorption		W	15		15	
Product specifications						
Dimensions	WxHxD	mm	700x600x215		700x600x215	
Net weight		Kg	16		16	
Sound pressure level at 1 m	H/M/L	dB(A)	38/33/27		38/33/27	
Volume of air treated	H/M/L	m ³ /h	400/320/270		400/320/270	
Connection diameter	Liquid/Gas	mm (inch)	6.35 (1/4) / 9.52 (3/8)			
	Condensate	mm	28		28	
Optional parts						
Wired control			M-V-CW-SD1-G (LCD) / M-V-CW-TW1-G (touch) / M-V-CW-HB2-G (simplified)			
Centralized control			M-V-CC-T255-G2 / M-V-CC-T32-G (simplified)			

Model			M-V-CNA-36-G		M-V-CNA-45-G		M-V-CNA-50-G	
Control (included)			Remote control					
Rated capacity	Cooling	kW	3.60		4.50		5.00	
	Heating	kW	4.00		5.00		5.50	
Electrical data								
Power supply		Ph-V-Hz	1-220~240V-50Hz					
Power absorption		W	20		40		40	
Product specifications								
Dimensions	WxHxD	mm	700x600x215		700x600x215		700x600x215	
Net weight		Kg	16		16		16	
Sound pressure level at 1 m	H/M/L	dB(A)	40/37/32		46/43/39		46/43/39	
Volume of air treated	H/M/L	m ³ /h	480/400/300		680/600/500		680/600/500	
Connection diameter	Liquid/Gas	mm (inch)	6.35 (1/4) / 12.74 (1/2)					
	Condensate	mm	28		28		28	
Optional parts								
Wired control			M-V-CW-SD1-G (LCD) / M-V-CW-TW1-G (touch) / M-V-CW-HB2-G (simplified)					
Centralized control			M-V-CC-T255-G2 / M-V-CC-T32-G (simplified)					