

FLOOR/CEILING

6 CAPACITIES

3.60~14.00 kW

COMPACT DESIGN

235 mm height for all models

WASHABLE FILTER

better air quality

I FEEL FUNCTION

SELF-DIAGNOSIS

CONTROLS

remote control included

optional wired control

M-V-FCA-361~1401-G



Model			M-V-FCA-361-G	M-V-FCA-561-G	M-V-FCA-711-G
Control (included)			Remote control		
Rated capacity	Cooling	kW	3.60	5.60	7.10
	Heating	kW	4.00	6.30	8.00
Electrical data					
Power supply		Ph-V-Hz	1-220~240V-50Hz		
Power absorption		W	40	75	75
Product specifications					
Dimensions	WxHxD	mm	870x235x665	870x235x665	1200x 235x665
Net weight		Kg	25	31	31
Sound pressure level at 1 m	H/M/L	dB(A)	36/32/28	44/41/38	44/41/38
Volume of air treated	H/M/L	m ³ /h	650/610/530/460	850/800/700/600	1300/1220/1090/940
Connection diameter	Liquid/Gas	mm (inch)	6.35 (1/4") / 12.74 (1/2")		9.52 (3/8") / 15.9 (5/8")
	Condensate	mm	17		17
Optional parts					
Wired control			M-V-CW-SD1-G (LCD) / M-V-CW-TW1-G (touch) / M-V-CW-HB2-G (simplified)		
Centralized control			M-V-CC-T255-G2 / M-V-CC-T32-G (simplified)		

Model			M-V-FCA-901-G	M-V-FCA-1121-G	M-V-FCA-1401-G
Control (included)			Remote control		
Rated capacity	Cooling	kW	9.00	11.20	14.00
	Heating	kW	10.00	12.50	16.00
Electrical data					
Power supply		Ph-V-Hz	1-220~240V-50Hz		
Power absorption		W	140	160	160
Product specifications					
Dimensions	WxHxD	mm	1200x235x665	1570x235x665	1570x235x665
Net weight		Kg	31	40	42
Sound pressure level at 1 m	H/M/L	dB(A)	47/43/39	47/44/42	50/48/44
Volume of air treated	H/M/L	m ³ /h	1500/1380/1200/1020	1800/1700/1540/1400	2100/2000/1800/1480
Connection diameter	Liquid/Gas	mm (inch)	9.52 (3/8") / 15.9 (5/8")		
	Condensate	mm	17		17
Optional parts					
Wired control			M-V-CW-SD1-G (LCD) / M-V-CW-TW1-G (touch) / M-V-CW-HB2-G (simplified)		
Centralized control			M-V-CC-T255-G2 / M-V-CC-T32-G (simplified)		